SHARP



Recommended Solutions:

Entry Simulators							
	WUXGA	1080p					
Model	ME403U	M401H					
Light Source	Lamp	Laser					
Brightness (lumens)	4,000	4,000					
Lensing (Throw Ratio)	Standard (1.2-2.0:1)	Standard (1.16-1.47:1)					
Ideal Screen Size	Up to 120"	Up to 120"					

Mid-Level Simulators							
	WUXGA			4K UHD			
Model	PE456USL	P547UL	P627UL	P601Q	P721Q		
Light Source	Laser	Laser	Laser	Laser	Laser		
Brightness (lumens)	4,500	5,400	6,200	6,000	7,200		
Lensing (Throw Ratio)	Short Throw (0.44:1)	Standard (1.23-2.0:1)	Standard (1.23-2.0:1)	Standard (1.25-2.0:1)	Standard (1.25-2.0:1)		
Ideal Screen Size	Up to 130"	Up to 140"	Up to 150"	Up to 150"	Up to 170"		

High-End Simulators							
	WUXGA			4K UHD			
Model	PV710UL	PA804UL	PA1004UL	X141Q	X171Q		
Light Source	Laser	Laser	Laser	Laser	Laser		
Brightness (lumens)	7,100	8,000	10,000	13,500	16,500		
Lensing (Throw Ratio)	Standard (1.46-2.95:1)	Short, Standard, Long (0.32-7.02:1)	Short, Standard, Long (0.32-7.02:1)	Short, Standard, Long (0.31-4.0:1)	Short, Standard, Long (0.32-4.0:1)		
Ideal Screen Size	Up to 170"	Up to 200"	Up to 230"	Up to 230"	Up to 230"		

